

ENTERPRISE IP CCTV

# VEO-B40-Z

2MP, 3MP, 4MP, IR 40m IP CAMERA



## HDTV

## ONVIF



2.8 - 12mm  
LENS

## HD megapixel



VIEW  
REMOTELY  
on your mobile  
device

For iPhone & Android  
search for "VEOControl"  
For iPad & Android Tablet  
search for "VEOControl"

### SPECIFICATIONS

Image Sensor	1/2.9" SONY 2.4MP
Pixels	1920*1080, 2048*1536, 2688*1520
Resolution	2.0MP, 3.0MP, 4.0MP
Lens	2.8mm - 12mm
ONVIF	YES
Protocol	HTTP, TCP/IP, FTP, NTP, RTSP, UDP, ...
P2P	YES
Masking	3 Zones
WDR	YES
S/N Ratio	≥52dB
Min. Illumination	0.01Lux
Motion Detection	YES
Scanning System	Progressive
Shutter Control	Auto
Shutter Speed	Auto
Back Light Compensation	Auto
Gain Control	Auto
White Balance	Auto
Day/Night	IR-CUT
IR Distance	40 m
Power Supply	12V DC
Current Draw (IR on)	300 mA
POE	IEEE 802.3af
Dimensions	Ø: 105.5 x H: 215.5mm
Housing	Weatherproof
Operation Temperature	-10°C ~ +50°C
Storage Temperature	-20°C ~ +60°C
Weight	1.5KG
Humidity	max 95%

### FEATURES

- Waterproof Bullet Camera
- H.264 & MJPEG dual-stream encoding
- 2, 3, 4 Megapixel progressive scan
- 2.8-12mm Manual Zoom Lens
- Day/Night, 2DNR, AWB, AGC, BLC
- IR range: 40M
- Size: Ø: 105.5mm x H: 215.5mm
- POE Built-in
- Weight: 1.5KG

